



# LIFE™

## Product Specifications

LDSDG-50

SAFE-D-GRIP

### Description

Safe-D-Grip is a non-skid additive that can be added to epoxies, sealers or top coats to produce a skid resistant surface.

### Use

Safe-D-Grip may be added to 3100 Epoxy, 14 Series, Stone Glaze, 4001, 10 Series or CRU so long as the following are considered.

1. Amount of skid resistance that is required
2. How the surface will be cleaned
3. Effects on performance of the sealer
4. Aesthetics

### Advantages

✓Skid resistance

**Package Size** 3.2 OZ., 1 lb, 5 lb, 50 lb, 110 lb.

In general you may add 3.2 oz. of Safe-D-Grip per gallon, 1 lb. per 5 gallons of 10 series, 4001 or Stone Glaze. For higher build and two-part coating systems such as the LD3100 Epoxy or LDCRU Urethane, use 1 lb. Safe-D-Grip per 3 gallons (40 oz. if measured by volume.) This will leave a consistent texture that is still fairly easy to clean. The actual skid resistance will be greatly effected by the existing texture of the surface you are covering and the thickness of the sealer applied. Do not exceed these amounts without consulting with Life Paint.

We strongly recommend that a test area be completed and approved before proceeding with the intended application. Life Paint assumes no responsibility for slippery surfaces. The texture is determined by the applicator and the customer. If additional skid resistance is required please contact Life Paint for recommendations.

### Technical Data

Tensile strength	125 to 200 psi.
Peel adhesion	20 lb./in.min.
Plate glass	20 lb./in.min.
Aluminum	20 lb./in.min.
Concrete	20 lb./in.min.

This product contains chemicals known to the State of California to cause cancer, birth defects and reproductive harm. The maximum V. O. C. of this product does not exceed 100 grams/liter. WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).